ProVision 5.2.0

ProVision 5.2.0 is a major release with new features.

PHP Compatibility

Please note that ProVision version 5.2.0 will require php version 5.6.

Contact 6connect at info@6connect.com to schedule a demo or get more information.

New Features

(CFR denotes customer requested)

Portable Gadgets

IM - 2165: Portable Gadgets are drop-in code snippets that use the ProVision API to bring in data to other systems or web pages.

Search results for "6connect"			
ID	Туре	Name	
451	resources	6connect	
3641	contacts	Leroy Jenkins	S
479	zones	6connect.cor	n
1598	records	1234.com	
1598	records	1234.com	
1598	records	1234.com	
1001	records	123ohsnap.c	om
All Types ᅌ		Search	Powered By 휽 6 connect

Currently, three Gadgets are available: Global Search, IPAM Search, and DHCP Search. Each Gadget comes with various options for display style, number of records return, or behavior. Additional client-side style customizations may be made to further integrate the gadget with company styles.

For more information, see Portable Gadgets and Getting Started With Portable Gadgets.

LDAP/AD integration – option for Native Groups

IM - 2163: LDAP Authentication now has an option for native groups that does not require the 6connect schema.

How to use native groups:

From the Admin Preferences page of ProVision, under Authentication Options, find the "LDAP Group Attribute" field. Enter the attribute name for your LDAP server's internal list of user groups (for example, "memberOf"). If this Group Attribute has been set, it will be used first for authentication, otherwise the 6connect schema will be used.

After setting up the Group Attribute, the authentication settings can be tested for a user via the Remote Authentication Tester on the Admin Preferences page.

Remote Authentication Tester

Remote Authentication Tester			
This diagnostic test	This diagnostic tests whether the above settings are functioning.		
Be sure to hit the 'U	pdate' button so your edits are reflected in the database.		
Login Method: Username:	Radius 🖨		
Password:			
	Test Login		

Authentication settings can now be checked for a user with the Remote Authentication Tester.

Select the Login Method (Radius or LDAP), enter the Username and Password for the user, and then click "Test Login".

Additional Features

DHCP Server Monitoring and Pool Utilization

IM - 2164: A DHCP Scan Server function is now available in the DHCP Management Gadget.

Scan Server provides a "Scan Now" button, which scans the DHCP server and returns found IPs under DHCP Pools.



The returned IPs are divided by Pools and IPv4/IPv6. Returned fields include MAC address, IP address, and name. The percentage utilization of IP space out of the available DHCP Pool space is also included at the top of the list.

esuits : 0 Hosts Found, 256 Hos			
: 0 Hosts Found, 256 Hos			
	sts Available. 100.00% Free		
lo Hosts Found			
ellaneous Addresses: fo	ound addresses which do no	ot match a linked DHCP Po	ool
Hostname	MAC	IPv4	IPv6
Jnknown Host	08:d8:33:93:87:70	10.1.10.35	
sep58bfea1164be	58:bf:ea:11:64:be	10.1.10.136	
Jnknown Host	00:0e:8f:88:5b:8f	10.1.10.82	
philips-hue	00:17:88:24:2e:8b	10.1.10.85	
Jnknown Host	00:0c:29:62:6c:57	10.1.10.59	
directv-hr44-b1550683	10:77:b1:55:06:84	10.1.10.30	
Jnknown Host	00:80:a3:91:47:ae	10.1.10.55	
ifx bulb	d0:73:d5:00:06:a6	10.1.10.86	
sonoszb	00:0e:58:1c:e0:0a	10.1.10.108	
ifx bulb	d0:73:d5:00:ae:e2	10.1.10.96	
ifx bulb	d0:73:d5:00:a8:43	10.1.10.87	
Jnknown Host	f4:b8:5e:00:7b:f3	10.1.10.89	
Jnknown Host	74:29:af:d6:ba:8d	10.1.10.32	
Jnknown Host	ec:e0:9b:b7:f3:15	10.1.10.51	
ifx bulb	d0:73:d5:00:20:51	10.1.10.81	
sonoszp	00:0e:58:ff:8e:82	10.1.10.109	
1pi4305e9	4c:0f:6e:90:7a:da	10.1.10.75	
Jnknown Host	74:75:48:08:bb:b1	10.1.10.77	
Jnknown Host	a0:02:dc:1c:c4:aa	10.1.10.103	
Jnknown Host	94:10:3e:4c:82:c9	10.1.10.79	
Jnknown Host	00:25:90:02:ff:42	10.1.10.58	
iving-room	c8:69:cd:2c:38:56	10.1.10.44	
kitchen	c8:69:cd:37:c9:bc	10.1.10.66	
phone6splus	7c:01:91:d1:34:f3	10.1.10.104	
nacbook	a8:66:7f:15:6b:85	10.1.10.39	
phone1	d8:bb:2c:7a:61:8e	10.1.10.37	
nac-mini	20:c9:d0:96:4e:9d	10.1.10.107	
pedroomappletv2	6c:94:f8:e1:b0:14	10.1.10.54	
nac-air	9c:f3:87:b1:5b:b6	10.1.10.90	
ivingroom	a4:67:06:64:b3:97	10.1.10.49	
aarons-imac	b8:09:8a:ba:dd:4f	10.1.10.34	
phone-88	5c:ad:cf:03:3b:66	10.1.10.45	
pad2	2c:1f:23:49:1f:93	10.1.10.84	
Jnknown Host	34:46:6f:0a:c5:a1	10.1.10.33	
)2aa01ac351309sc	18:b4:30:0c:c5:27	10.1.10.31	
Jnknown Host	00:11:32:16:29:ef		2607:fae0:6000::514c
Jnknown Host	20:61:73:79:6e:ff		2607:fae0:6000::5e35
Jnknown Host	88:1f:a1:2a:d7:71		2607;fae0;60005065

DHCP Current Pushed Configuration display / Improved error handling

CFR/IM - 2248: Improved DHCP error handling for cases of server misconfigurations.

Also added a display under the DHCP Management Gadget to view the last successfully pushed configuration. It does not reflect unpushed changes or failed pushes.

To view the configuration text, navigate to the DHCP Management Gadget for the desired DHCP server, then click on "Current Pushed Configuration". For additional details on the DHCP Gadget and Pushing, see our DHCP Documention.

Current Pushed Configuration	
This is the last successfully pushed configuration. It does not reflect unpushed changes or failed pushes.	
# DHCP Config for ISC.	
authoritative; option domain-name-servers dev2.6connect.com; default-lease-time 600; max-lease-time 7200; local-port 67; local-port 67;	
subnet 10.8.0.0 netmask 255.255.255.0 { range 10.8.0.0 10.8.0.255; }	
subnet 10.8.1.0 netmask 255.255.255.252 { range 10.8.1.0 10.8.1.3; }	
e Configuration Push Configuration	

Resource Query performance and security enhancements

IM - 2166: Resource Query has undergone various performance and security enhancements.

Direct Assign and Smart Assign enhancements

IM - 2160: Direct Assign and Smart Assign are now transaction-safe atomic operations, improving scalability of calls.

Revamped installer/upgrader

ProVision Interactive Installation & Debugger		
This is the ProVision Interactive Installation & Debugger page. If you're seeing this good job! You already have PHP and Apache working. Each of the following steps will ensure that essential server features are installed and configured. At each step all items marked in red must be corrected before proceeding to the next. If you have any questions about correcting a mis-configuration, please contact support@6connect.com.		
For complete install instructions read the installation documentation.		
Step 1: HTTPS		
HTTPS: Enabled		
Step 1: Passed.		
Step 2: PHP Co	onfiguration	
PHP Version:	5.6.4-4ubuntu6.4	
PHP Errors:	Error reporting off	
PHP Error Level:	22527	
Step 2: Passed.		

IM - 2167: install/configTest.php has been updated to provided a smoother install or upgrade experience. The installer now provides clear stepby-step checks for required dependencies and settings. At each step, all items marked in red must be corrected before proceeding to the next. If you have any questions or require assistance correcting a mis-configuration, please contact support@6connect.com.

URL Custom Field Type

CFR / IM - 2133: A URL custom field type has been added to the available fields when creating a Section. The URL field checks if the field value contains "https://www.", and if not, adds it as a prefix to the field value, providing a clickable link on the Resource's Entry page.

To add the URL field to a Section, edit the desired Section, then drag and drop the URL field type into the Section's field list and save your changes.

	Tables	
Name	lext Input	
Address		
	Text Area	
Billing Start Date		
Billing End Date		
URL		
	URL	
	Drag and drop	
	into field list	
	Choice Box	
	Option one	
	Radios	
	 Option one 	
	Option two	
	Checkboxes	
	Option one	

Edit the Entry page for the desired Resource (that is associated with the previously edited Section), and populate the URL field with desired address.

Note: The URL field will automatically prefix the value with "https://www." if it is not already included in the address. However, be sure to include the Top Level Domain.

After the field is filled out, click "Save".

Basic Information	Name (required) aNewEntry Parent TLR		Section aNewSection Category Customer	
Fields				
	Name	ExampleEntry		
	Address	123 Main		
	Billing Start Date	1-12-2016		
	Billing End Date	5-20-2016		
	URL	6connect.com		
	Some fields are hidden. Find out	why.		
Delete				View Save

The URL field will be then accessible as a clickable link that opens in a new tab.

Fields	
Name: ExampleEntry	
Address: 123 Main	
Billing Start Date: 1-12-2016	
Billing End Date: 5-20-2016	
URL: 6connect.com	
	Clone Add Child Edit

Bug Fixes/Improvements

- IM 1782: IPAM, DNS, and VLAN Tags now consider spaces and letter case to prevent duplicate entries.
- IM 2061: Resolved duplication of Resource IDs in IPAM / VLAN Manage that occurred when the "Assigned" header was clicked.
- IM 2113-2115: Improved handling of limited permissions for adding DHCP servers.
- IM 2138: Resolved a hover issue when viewing the VLAN Tags chart in Firefox.
- IM 2142: The "Templates" link in the IPAM / VLAN manage action menu is once again functional.
- IM 2154: In the Dashboard Activity Chart Widget, clicking on DNS activity now shows detail text.
- IM 2156: Single-block IPAM Updates made through the API now respect the tags_action parameter.
- IM 2157: Resolved an issue where deleting an IP aggregate could result in orphan DHCP pools under that aggregate.
- IM 2158: Updated IPAM API parameter "isAggregate" to filter correctly when set to false.
- IM 2168: Revised the "Contact Us" Widget to have "feeback@6connect.com" as the default feedback address.
- IM 2173: The "Comment" section for local contacts no longer duplicates upon editing.
- IM 2176: Resolved an issue that would prevent some one-time scheduler tasks from running.
- IM 2183: IPAM Manage "Generic Code" filter header now updates with user provided value.
- IM 2184: Resolved issue where "LIR" and "Region" were not able to be de-selected when editing an IPAM block.
- IM 2187: Updated IPAM error message "(Block) is already assigned to (Resource)" to include both resource name and number.
- IM 2198: Resolved issue on a resource's Entry page where an extremely long breadcrumb would expand outside its boundary.
- IM 2200: Fixed an issue where unassigning a child block with skip hold could cause the parent block's sibling to lose assignment.
- IM 2201: Revised the DNS Gadget Zone Delegation "Delete" icon.
- IM 2204: When "Merge after Unassign" is enabled in IPAM Configuration, sibling blocks will no longer merge if one block is in the holding tank.
- IM 2205: When "Merge after Unassign" is enabled in IPAM Configuration, blocks will now automatically refresh after merging occurs.
- IM 2206: Resolved an error that prevented the region from display for newly created top-level aggregates.
- IM 2209: VLAN Chart mouseover functions once again work in Firefox.
- IM 2210: Updated the resource selector in Edit Groups to be a searchable list.
- IM 2218: Smart Browse is now smarter in assigning blocks when duplicate 1918 aggregates exist.
- IM 2221: Removed the radio toggle for text / html email options under Peering Email Tech /NOC / Policy Action Menu items.

- IM 2225: The IPAM Filter Aggregate List box will now be hidden if no aggregates are viewable.
- IM 2227: Cleaned up error messages when adding a user.
- IM 2231: Fixed an issue that would prevent updates to IPAM blocks propagating to children if tags were included.
- IM 2232: Resolved error in IPAM Manage that would temporarily hide the VLAN information when selecting "Unassign / Skip Hold" on a block.
- IM 2233: Improved IPAM Tab loading time.